

Engine series	Power range HP / kW	Rpm range	Displacement, L	Dimensions, L/W/H, mm	Dry weight, kg	Identifying code by GOST 10150-88
QSM11	250 - 400 / 186 - 298	1800 - 2100	10,8	1306 / 914 / 1280	914	64H12,5/14,7
QSX15	350 - 600 / 261 - 447	1800 - 2100	15	1443 / 1080 / 1238	1440	64H13,7/16,9
QSK19L	560 - 800 / 418 - 597	1800 - 2100	19	1679 / 1080 / 1616	2075	64H15,9/15,9
QSK19R	650 - 755 / 485 - 563	1800 - 2100	19	1680 / 1930 / 860	2020	64H15,9/15,9
QST30L	760 - 1200 / 567 - 895	1800 - 2100	30,5	1933 / 1506 / 1706	3375	124H14/16,5
QSK38L	1200 - 1500 / 895 - 1119	1800	37,8	2206 / 1452 / 1846	4150	124H15,9/15,9
QSK45L	1350 - 1800 / 1007 - 1340	1800	45	2372 / 1572 / 1880	6125	124H15,9/19
QSK50L	1500 - 2000 / 1119 - 1491	1800	50,3	2787 / 1506 / 1780	6575	164H15,9/15,9
QSK60L	2000 - 2700 / 1491 - 2013	1800	60	2787 / 1572 / 1960	9220	164H15,9/19
QSK78L	3300 / 2461	1800	77,6	2961 / 1605 / 1860	10950	184H17/19
QSK95L	3600 - 4200 / 2685 - 3135	1800	95	3680 / 1650 / 2410	13300	164H19,1/21